

# ANGULATION CORRECTIVE SYSTEM (ACS)

ACS abutments are for precision manufactured CAD/CAM screw retained restorations where angulation of the screw access hole is required for improved aesthetics and/or function.

The ACS system permits angulation of the screw access hole up to 20 degrees. This is achieved with the aid of a special designed abutment screw & screwdriver (hand or ratchet) to facilitate precise

tightening of the abutment screw at the required torque.

- The ACS system offers the dental technician control over the desired position of the screw access hole, this is beneficial in the anterior segment to ensure the screw access hole is in the cingulum area without compromising the buccal aspect of the soft tissue with the use of an angulated abutment.
- In the posterior segment the ACS system can offer a mesially inclined screw access hole for easy entry in cases where there is limited inter occlusal space.
- Angulation of the screw access hole to the palate or lingual aspect in the posterior zone will facilitate an uncompromised occlusal surface for improved aesthetics & function.

NARROW PLATFORM	
Engage	LENGTH = 4 MM
	1mm      3mm
Non Engage	LENGTH = 4 MM
	1mm      3mm

STANDARD PLATFORM	
Engage	LENGTH = 4 MM
	1mm      3mm
Non Engage	LENGTH = 4 MM
	1mm      3mm

CONICAL PLATFORM	
Engage	LENGTH = 4 MM
	1mm      3mm
Non Engage	LENGTH = 4 MM
	1mm      3mm

Screw NP	Screw SP	Screw PCA
80-70038	80-70037	80-72001

Manual Hex Driver	Hex Driver for Ratchet
60-70152	60-70153

